

Instron® Industrial Series HVL Models are designed for high-capacity tension, compression, bend/flex, and shear testing. Available in 2000 kN (450,000 lbf) capacity in standard and wide models, this frame features a dual test space. Understanding the critical importance of operator safety, Instron's HVL Models incorporate high-quality materials, components, and craftsmanship.

### Features and Benefits

- Two test space design makes changing between tension and compression testing safer and more efficient – no need to remove heavy fixtures
- Long test stroke accommodates a variety of test fixtures and applications
- Semi-open crossheads with hydraulic lever action grips for easy specimen loading and clamping
- 5900 Productivity panel with multiple function keys and displays improves ergonomics and allows the operator to perform common testing functions and view key test information without returning to the computer
- Powerful, yet user-friendly materials testing software provides repeatable and reproducible results for simple to sophisticated testing requirements
- Variable pressure hydraulic power supply provides pressure on demand, reducing heat generation, increasing oil life, and eliminating the need for water cooling
- External hydraulic power supplied with convenient table top working surface
- Available capacities:
  - 2000 kN (450,000 lbf)

### Testing Applications

- Metals—Bar, Plate, Pipe & Tube, Rebar, Structural
- Wire—Rod, Strand
- Fasteners
- Concrete—Cubes, Cylinders, Beams
- Wood

### Standards

HVL Models conform to many international standards:

- ASTM A370, A615, C39, C109, E4, E8, E9, E83, E290, F606
- ISO 6892-1, 6892-2, 7438, 9513, 15630-1
- EN10002-1, 10002-2, 10002-4
- JIS Z2248
- BS4449



		400HVL	400WHVL
Load Capacity	kN	2,000	2,000
	kgf	200,000	200,000
	lbf	450,000	450,000
Maximum Test Speed	mm/min	114	114
	in/min	4.5	4.5
Actuator Stroke	mm	228	304
	in	9	12
Horizontal Opening (between columns)	mm	609	762
	in	24	30
Floor Space Requirements (W × D) *Pit Mounting	mm	1296 × 712	1279 × 962*
	in	51 × 28	56 × 73

#### Tension Opening

G2A	mm	76 - 838	76 - 1828
	in	3 - 33	3 - 72
G2D	mm	76 - 1753	-
	in	3 - 69	-

#### Compression Opening

G1A	mm	51 - 812	25 - 1778
	in	2 - 32	1 - 70
G1D	mm	51 - 1727	-
	in	2 - 68	-
G2A	mm	254 - 1016	280 - 2032
	in	10 - 40	11 - 80
G2D	mm	254-1727	-
	in	10-68	-

#### Compression Table Size (W × D)

G2A	mm	609 × 762	762 × 762
	in	24 × 30	30 × 30
G2D	mm	609 × 762	-
	in	24 × 30	-

#### Maximum Operating Height

G2A	mm	3417	3976
	in	134.5	156.5
G2D	mm	4331	-
	in	170.5	-

#### Tension Specimen Lengths

		400HVL	400WHVL
G2A	mm	448 - 1134	448 - 2124
	in	17.6 - 44.6	17.6 - 83.6
G2D	mm	448 - 1753	-
	in	17.6 - 69	-

#### Net Weight

G2A	kgs	6,035	8,325
	lbs	13,300	18,350
G2D	kgs	6,870	-
	lbs	15,140	-

## Common Specifications

Data Acquisition Rate by Software  
Up to 1 kHz synchronous on load and strain

Load Measurement Accuracy  
± 0.5% of reading down to 1/500 of load cell capacity

Strain Measurement Accuracy  
Meets or surpasses the following standards: ASTM E8, ISO 9513, and EN 10002-4

Position Measurement Accuracy  
6.35 µm (0.00025 in) resolution. Position accuracy: ±1% or 0.254 mm (0.01 in) displacement (whichever is greater).

Hydraulic Power Supply  
Voltage Options  
208/230 VAC, 3 Ph, 50/60 Hz  
380/400/415 VAC, 3 Ph, 50/60 Hz  
460 VAC, 3 Ph, 50/60 Hz

## Accessories

- In-head Grip Jaws—flat, round
- Tensile Grips—button head, threaded-end
- Fastener Fixtures
- Compression Platens—plane and self-aligning
- Bend/Flex and Shear fixtures
- Extensometers, Deflectometers
- Low-Capacity Load Cells
- Interlocked Safety Enclosures
- Tee Slot Tables
- Furnaces

[www.instron.com](http://www.instron.com)



Worldwide Headquarters  
825 University Ave, Norwood, MA 02062-2643, USA  
Tel: +1 800 564 8378 or +1 781 575 5000

Instron Industrial Products  
900 Liberty Street, Grove City, PA 16127, USA  
Tel: +1 724 458 9610

Instron is a registered trademark of Illinois Tool Works Inc. (ITW). Other names, logos, icons and marks identifying Instron products and services referenced herein are trademarks of ITW and may not be used without the prior written permission of ITW. Other product and company names listed are trademarks or trade names of their respective companies. Copyright © 2017 Illinois Tool Works Inc. All rights reserved. All of the specifications shown in this document are subject to change without notice.